

ProMinent® Sigma/ 3

Diaphragm dosing pump

01.12.2015

Master pricelist Heidelberg (valid as of 01.01.2016)

S3CbH	Ident code	Price 2016 Euro	Ident code	Option Description	Price 2016 Euro
	120145 PVT S000UA000S00	3 162,00	S000UA000S000	Basic type	
	120145 SST S000UA000S00	3 592,00	S	Multi-layer safety-diaphragm with opt. rupture dis.	0,00
	120190 PVT S000UA000S00	3 162,00	A	Multi-layer safety-diaphragm with el. rupture signalisation	116,00
	120190 SST S000UA000S00	3 592,00	HH	Diaphragm for hygienic head	on request
	120270 PVT S000UA000S00	3 162,00	.0	without bleed valve, without valve spring	0,00
	120270 SST S000UA000S00	3 592,00	.1	without bleed valve, with valve spring	16,00
	070410 PVT S100UA000S00	3 514,00	.2	with bleed valve, seal FPM, without valve spring	89,00
	070410 SST S100UA000S00	3 899,00	.3	with bleed valve, seal FPM, with valve spring	106,00
	070580 PVT S100UA000S00	3 514,00	PVT. 4/6	PVT: pressure relief valve, FPM / EPDM, without spring	166,00
	070580 SST S100UA000S00	3 899,00	SST. 4/6	SST: pressure relief valve, FPM / EPDM, without spring	288,00
	040830 PVT S100UA000S00	3 514,00	PVT. 5/7	PVT: pressure relief valve, FPM / EPDM, with spring	184,00
	040830 SST S100UA000S00	3 899,00	SST. 5/7	SST: pressure relief valve, FPM / EPDM, with spring	307,00
			.8	with bleed valve, seal EPDM, without valve spring	89,00
			.9	with bleed valve, seal EPDM, with valve spring	106,00
			HH	Hygienic head with tri-clamp connection (max. 10 bar)	on request
			.0	Standard thread connector	0,00
			.1	union nut and insert PVC	16,00
			.2	union nut and insert PP	32,00
			.3	union nut and insert PVDF	61,00
			.4	union nut and insert SS	176,00
			.7	union nut and tube nozzle PVDF	66,00
			.8	union nut and tube nozzle SS	205,00
			.9	union nut and welded sleeve stainless steel	176,00
			.0	with ProMinent logo (standard)	0,00
			.1	without ProMinent logo	12,00
			F	physiologically harmless (FDA)	100,00
			M	modified	on request
			U	1 ph, 100 - 230 V ± 10 %, 240 V ± 6 %, 50/60 Hz	0,00
			A	2 m Europe	0,00
			B	2 m Switzerland	9,00
			C	2 m Australia	12,00
			D	2 m USA	9,00
			1	open end, 2 m	9,00
			2	open end, 5 m	12,00
			.0	no relay	0,00
			.1	fault indicating relay (230V - 8A)	65,00
			.3	fault indicating relay + pacing relay (24V - 100mA)	78,00
			.8	0/4-20 mA output + fault indicating/pacing relay (24 -100mA)	123,00
			.0	manual + extern contact + pulse control	0,00
			.1	manual + ext. cont. + pulse contr. + anal. + metering profiles	126,00
			.6	as 1 + Profibus DP-Schnittstelle, M 12	461,00
			C	as 1 + CANopen-pump	87,00
			D	as 1 + Dulcomarin-CANopen-pump	87,00
			.0	without overload shutdown	0,00
			.1	with overload shutdown	98,00
			S	operating unit (HMI) (0,5m cable)	0,00
			.1	operating unit (HMI) + 2 m cable	45,00
			.2	operating unit (HMI) + 5 m cable	55,00
			.3	operating unit (HMI) + 10 m cable	73,00
			X	without operating unit (HMI)	-150,00
			.0	without access code	0,00
			.1	with access code	0,00
			DE	German	IT - Italian
			EN	English	NL - Dutch
			ES	Spanish	PL - Polish
			FR	French	PT - Portuguese
			.01	CE	0,00

Drive unit:

120145 XAX XXX0UX000S00 2 696,00

040830 XAX XXX0UX000S00 2 696,00